



Fire Protection for System and Data Cabinets

PFP

Plug-In-Fire Protection



FESD Object-Fire-Protection System - Plug-In Model

**BASIC DATA**

Article Number: PM 600 000

Master-slave networking over CAN bus 30 slave
Extinguishing range control
Optical smoke alarm
Two-alarm dependence
Active fire recognition
Argon extinguishing agent (2.1 m³ extinguishing volume)
Interruption-free power supply
Solenoid valve
Primary output monitoring
Event logbook
SNMP (master only)
Extinguish standard interface (DSI) (master only)
Climate monitoring (humidity/temperature)



Option
Option
Option

TECHNICAL DATA

Input voltage: 230V AC
Power: 25W
USV 2.2 Ah (4 hours)
2 x 5l argon (200 bar)
Alarm: 95 dB

Dimensions:	Height:	4HE (177 mm)
	Width:	19" plug-in (installation width with telescope rails 442 mm)
	Depth:	640/ installation depth 600 mm
	Weight:	32 kg

OPERATION

Cursor keys (master only)
4 x 20 character LCD display (master only)
Status indication by means of 6 light emitting diodes
Acoustic alarm
Diagnostic, maintenance and start-up software (Windows)

**INPUTS**

RS232 constructor interface
Extinguish command from BMZ (DSI) (master only)
Door contact
Manual alarm

OUTPUTS

4 programmable floating contacts
1 floating server down change-over contact
Disturbance alarm to BMZ (DSI) (master only)
Alarm message to BMZ (DSI) (master only)



The technical data were gleaned with great care; we are nevertheless not liable for possible consequences of use. Right of modification reserved.